



# Technical Specifications VOYAGEUR II



## CONSOLE

**Neve VR** in line 48 inputs 48 outputs routing, Flying fader and recall  
*Premix option* : 2 x **ATI 8MX2**, 8 x channels mixers

## MONITORING

**ATC / MDF** 3 ways active  
3 x **Amcrom MA 2400** amps  
*Alternate monitor* : **Genelec 1031**, **Mackie HR 824**.

## PROCESSING

48 x **comp / gate** in Neve VR channels  
2 x **Summit TLA 100** tube leveller  
1 x **UREI 1176 LN**  
2 x **NEVE 34268** stereo lim comp  
1 x **SSL G384** mix comp  
1 x **Orban deesser 526 A**

## REVERBERATION / DELAY / MULTIFX

1 x **Lexicon 480 L**  
2 x **Lexicon PCM 70**  
1 x **Lexicon PCM 42**  
1 x **Eventide H 3000**  
1 x **Yamaha SPX 990**  
2 x **Sony V 77**

## MULTITRACK RECORDER

2 x **Pro-Tools HD** 48 in/out

## 2 TRACKS RECORDERS

1 x **Sony PCM 7030** time code DAT  
1 x **Sony PCMR 500** DAT  
1 x **Tascam CDRW 2000** CD Burner

## VIDEO

1 x **Tektronix TSG 111** Pal Generator  
1 x **AVS** Distributor Video 2 x 4  
2 x **Sony Monitors** in front of the desk  
1 x **Sony monitor** in production room  
1 x **Sony colour CDD** camera for stage vision

## SPLITTING

60 x **Channels of Jensen** passive splitter with custom 48 V phantom power.